

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

1. Identification

1.1. Product identifier

Product Identity Stainless Flux-Cored Wire

Alternate Names MASTERCOR E307T1-1/4, E308/308HT0-1/4, E308/308HT1-1/4, E308LT0-1/4, E308LT1-1/4, E309/309HT0-1/4, E309/309HT1-1/4, E309LT0-1/4, E309LT1-1/4, E309LMoT1-1/4, E310T1-1/4, E312T1-1/4, E316/316HT0-1/4, E316/316HT1-1/4, E316LT0-1/4, E316LT1-1/4, E317LT1-1/4, E347T1-1/4, E410T1-1/4, E410NiMoT1-1/4, E2209T1-1/4, E2553T1-1/4, E2594T1-1/4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Stainless steel flux-cored welding wire - AWS/SFA 5.22

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Midalloy
630 Axminister Drive
St. Louis, MO 63026

Emergency

24 hour Emergency Telephone No. (636) 349-6000

Customer Service: Midalloy (800) 776-3300

2. Hazard(s) identification

2.1. Classification of the substance or mixture

| | |
|--------------------|--|
| Acute Tox. 4;H302 | Harmful if swallowed. |
| Skin Irrit. 3;H316 | Causes mild skin irritation. (Not adopted by US OSHA) |
| Eye Irrit. 2;H319 | Causes serious eye irritation. |
| Skin Sens. 1;H317 | May cause an allergic skin reaction. |
| Resp. Sens. 1;H334 | May cause allergy or asthma symptoms of breathing difficulties if inhaled. |
| Carc. 2;H351 | Suspected of causing cancer. |
| STOT RE 1;H372 | Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (lungs) |

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

H302 Harmful if swallowed.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

P285 In case of inadequate ventilation wear respiratory protection.

[Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P330 Rinse mouth.

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|--|--------|
| Iron CAS Number: 0007439-89-6 | 50 - 75 | Not Classified | [1] |
| Chromium compounds (as Cr (III)) CAS Number: 0007440-47-3 | 10 - 25 | Skin Sens. 1;H317 Resp. Sens. 1;H334 Eye Irrit. 2;H319 Aquatic Chronic 4;H413 | [1][2] |
| Nickel CAS Number: 0007440-02-0 | 10 - 25 | Carc. 2;H351 STOT RE 1;H372 Skin Sens. 1;H317 Aquatic Chronic 3;H412 | [1][2] |
| Titanium dioxide CAS Number: 0013463-67-7 | 5 - 10 | Not Classified | [1][2] |
| Zircon CAS Number: 0014940-68-2 | 1 - 5 | Not Classified | [1] |
| Feldspar CAS Number: 0068476-25-5 | 1 - 5 | Not Classified | [1] |
| Manganese compounds (as Mn) CAS Number: 0007439-96-5 | 1 - 5 | Not Classified | [1][2] |
| Molybdenum CAS Number: 0007439-98-7 | 1 - 5 | Not Classified | [1][2] |
| Niobium CAS Number: 0007440-03-1 | 1 - 5 | Not Classified | [1] |
| Aluminum oxide CAS Number: 0001344-28-1 | 1 - 5 | Not Classified | [1][2] |
| Sodium fluoride CAS Number: 0007681-49-4 | 1 - 5 | Acute Tox. 3;H301 Eye Irrit. 2;H319 Skin Irrit. 2;H315 | [1][2] |

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Immediately flush the eyes with large amounts of water for at least 15 minutes, alternately lifting the upper and lower eyelids. After 5 minutes, if appropriate, remove contact lenses and continue flushing the eyes for an additional 15 minutes. Call a physician at once.

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion Do not induce vomiting. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview Inhalation: Inhalation of dust may cause respiratory irritation. Chromium and certain compounds of chromium have been reported to cause damage to the lungs, resulting in cumulative damage.
Ingestion: May cause gastric disturbances.
Skin: May cause sensitization on repeated contact. Dermatitis has been reported from repeated contact with chromium compounds.
Eyes: Contact may cause irritation.

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Electric arc welding may create one or more of the following health hazards:
Fumes and gases can be dangerous to your health.
Arc rays can injure eyes and burn skin.
Electric shock can kill.

See section 2 for further details.

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes mild skin irritation. (Not adopted by US OSHA)

Ingestion Harmful if swallowed.

Chronic effects **Effects of Overexposure:** Fumes and gases can be dangerous to your health.
Short-Term (Acute) Exposure to welding fumes may result in discomfort such as dizziness, nausea, or dryness or irritation of nose, throat, or eyes.
Long-Term (Chronic) Overexposure may lead to siderosis (iron deposits in the lung) and is believed by some investigators to affect pulmonary function.

5. Fire-fighting measures

5.1. Extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Welding fumes cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded and the process, procedures and electrodes used. Other conditions which influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), number of welds and volume of work area, quality and amount of ventilation, position of welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the electrode is consumed, the fume and gas decomposition products are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition products, not the ingredients in the electrode, are important. Decomposition products include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3 plus those from base metal, coating, etc. as noted above. These components are virtually always present as complex compounds and not as metals (Characterization of Arc Welding Fume; American

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

Welding Society).

Reasonably expected fume constituents from these products would include fluorides and complex oxides of iron, manganese, and silicon and when present, nickel chromium, molybdenum and copper. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc.

One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the welder's helmet, if worn, or in the worker's breathing zone. ANSI/AWS F1.1, available from the American Welding Society, P.O. Box 351040, Miami, FL 33135.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Welding arc and sparks can ignite combustibles and flammables. Refer to American National Standard Z49.1 for fire prevention during the use of welding and allied procedures.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use exhaust system to clear welding fumes. Make sure that inhaled air does not contain fume constituents above permissible exposure levels.

NOTE: for additional safety information see American Standard Z49.1-1983, Safety in Welding and Cutting, and the Welding Handbook, both available from AWS, Inc., 550 N.W. LeJeune Rd., P.O. Box 351040, Miami, FL 33135, Phone (305) 443-9353.

6.2. Environmental precautions

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent waste from contaminating surrounding environment. Discard any product residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with Federal, State and Local regulations.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: No data available.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|----------------------------------|----------|--|
| 0001344-28-1 | Aluminum oxide | OSHA | TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp) |
| | | ACGIH | No Established Limit |
| | | NIOSH | no established RELs |
| | | Supplier | No Established Limit |
| 0007439-89-6 | Iron | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0007439-96-5 | Manganese compounds (as Mn) | OSHA | C 5 mg/m ³ *See specific listings for specific compounds. |
| | | ACGIH | TWA: 0.2 mg/m ³ R |
| | | NIOSH | TWA 1 mg/m ³ ST 3 mg/m ³ *See specific listings for specific compounds. |
| | | Supplier | No Established Limit |
| 0007439-98-7 | Molybdenum | OSHA | TWA 15 mg/m ³ [*Note: The PEL also applies to other insoluble molybdenum compounds (as Mo).] |
| | | ACGIH | TWA: 0.5 mg/m ³ (soluble)TWA: 3 mg/m ³ (insoluble respirable) 10 mg/m ³ (insoluble inhalable) |
| | | NIOSH | No established RELs |
| | | Supplier | No Established Limit |
| 0007440-02-0 | Nickel | OSHA | TWA 1 mg/m ³ [*Note: The PEL does not apply to Nickel carbonyl.] |
| | | ACGIH | Insoluble TWA: 0.05 mg/m ³ A1, 1, (I)Soluble TWA: 0.05 mg/m ³ A1, 1, 2B, (I) |
| | | NIOSH | Ca TWA 0.015 mg/m ³ [*Note: The REL does not apply to Nickel carbonyl.] |
| | | Supplier | No Established Limit |
| 0007440-03-1 | Niobium | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0007440-47-3 | Chromium compounds (as Cr (III)) | OSHA | TWA 1 mg/m ³ [*Note: The PEL also applies to insoluble chromium salts.] |
| | | ACGIH | TWA: 0.5 mg/m ³ (III) |
| | | NIOSH | TWA 0.5 mg/m ³ |
| | | Supplier | No Established Limit |
| 0007681-49-4 | Sodium fluoride | OSHA | TWA 2.5 mg/m ³ [*Note: The REL also applies to other inorganic, solid fluorides (as F).] |
| | | ACGIH | No Established Limit |
| | | NIOSH | TWA 2.5 mg/m ³ [*Note: The REL also applies to other inorganic, solid fluorides (as F).] |
| | | Supplier | No Established Limit |

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

| | | | |
|--------------|------------------|----------|---|
| 0013463-67-7 | Titanium dioxide | OSHA | TWA 15 mg/m ³ |
| | | ACGIH | TWA: 10 mg/m ³ 2B, Revised 2006, |
| | | NIOSH | Footnote ca |
| | | Supplier | No Established Limit |
| 0014940-68-2 | Zircon | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0068476-25-5 | FELDSPAR | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|----------------------------------|--------|---|
| 0001344-28-1 | Aluminum oxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007439-89-6 | Iron | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007439-96-5 | Manganese compounds (as Mn) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007439-98-7 | Molybdenum | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007440-02-0 | Nickel | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: Yes; Suspected: Yes |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0007440-03-1 | Niobium | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007440-47-3 | Chromium compounds (as Cr (III)) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0007681-49-4 | Sodium fluoride | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

| | | | |
|--------------|----------|------|--|
| 0014940-68-2 | Zircon | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0068476-25-5 | FELDSPAR | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

| | |
|-----------------------------|---|
| Respiratory | Use respirable fume respiratory or air supplied respirator when welding in a confined space or where local exhaust or ventilation does not keep exposure below the recommended exposure limit. |
| Eyes | Wear helmet or use face shield with filter lens. Provide protective screens and flash goggles, if necessary, to shield others. As a rule of thumb, start with a shade that is too dark to see the weld zone. Then go to the next lighter shade, which gives sufficient view of the weld zone. |
| Skin | Wear hand, head, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons hats, shoulder protection, as well as dark substantial clothing. Train the welder not to touch live electrical parts and to insulate himself from work and ground. |
| Engineering Controls | Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases from the worker's breathing zone and the general area. Train the welder to keep his head out of the fumes. |
| Other Work Practices | Read and understand the manufacturer's instructions and the precautionary label on the product. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. |

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

| | |
|---|--|
| Appearance | Solid |
| Odor | Not Specified |
| Odor threshold | Not determined |
| pH | Not Measured |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | Not Measured |
| Flash Point | Not Measured |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured |
| Vapor pressure (Pa) | Not Measured |
| Vapor Density | Not Measured |
| Specific Gravity | Not Measured |

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

| | |
|--|--------------|
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | Not Measured |

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Welding fumes cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded and the process, procedures and electrodes used. Other conditions which influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), number of welds and volume of work area, quality and amount of ventilation, position of welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the electrode is consumed, the fume and gas decomposition products are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition products, not the ingredients in the electrode, are important. Decomposition products include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3 plus those from base metal, coating, etc. as noted above. These components are virtually always present as complex compounds and not as metals (Characterization of Arc Welding Fume; American Welding Society).

Reasonably expected fume constituents from these products would include fluorides and complex oxides of iron, manganese, and silicon and when present, nickel chromium, molybdenum and copper.

Gaseous reaction products may include carbon monoxide and carbon dioxide.

Ozone and nitrogen oxides may be formed by the radiation from the arc.

One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the welder's helmet, if worn, or in the worker's breathing zone. ANSI/AWS F1.1, available from the American Welding Society, P.O. Box 351040, Miami, FL 33135.

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

11. Toxicological information

Acute toxicity

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|--|-------------------------------|----------------------------------|---------------------------------|-------------------------------------|--------------------------|
| Iron - (7439-89-6) | 30,000.00, Rat - Category: NA | No data available | No data available | No data available | No data available |
| Chromium compounds (as Cr (III)) - (7440-47-3) | 422.00, Rat - Category: 4 | No data available | No data available | No data available | No data available |
| Nickel - (7440-02-0) | No data available | No data available | No data available | No data available | No data available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA | No data available |
| Zircon - (14940-68-2) | No data available | No data available | No data available | No data available | No data available |
| FELDSPAR - (68476-25-5) | No data available | No data available | No data available | No data available | No data available |
| Manganese compounds (as Mn) - (7439-96-5) | 9,000.00, Rat - Category: NA | 500.00, Rabbit - Category: 3 | 19.00, Rat - Category: 4 | No data available | No data available |
| Molybdenum - (7439-98-7) | No data available | No data available | No data available | No data available | No data available |
| Niobium - (7440-03-1) | No data available | No data available | No data available | No data available | No data available |
| Aluminum oxide - (1344-28-1) | 5,000.00, Rat - Category: 5 | No data available | No data available | No data available | No data available |
| Sodium fluoride - (7681-49-4) | No data available | No data available | No data available | No data available | No data available |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification | Category | Hazard Description |
|-------------------------------|----------|--|
| Acute toxicity (oral) | 4 | Harmful if swallowed. |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | --- | Not Applicable |
| Skin corrosion/irritation | 3 | Causes mild skin irritation. (Not adopted by US OSHA) |
| Serious eye damage/irritation | 2 | Causes serious eye irritation. |
| Respiratory sensitization | 1 | May cause allergy or asthma symptoms of breathing difficulties if inhaled. |
| Skin sensitization | 1 | May cause an allergic skin reaction. |
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | 2 | Suspected of causing cancer. |
| Reproductive toxicity | --- | Not Applicable |

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

| | | |
|------------------------|-----|---|
| STOT-single exposure | --- | Not Applicable |
| STOT-repeated exposure | 1 | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | --- | Not Applicable |

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|--|----------------------------|----------------------------|---------------------------------------|
| Iron - (7439-89-6) | Not Available | Not Available | Not Available |
| Chromium compounds (as Cr (III)) - (7440-47-3) | 77.50, Pimephales promelas | 1.20, Daphnia magna | 580.00 (72 hr), Chlorella pyrenoidosa |
| Nickel - (7440-02-0) | Not Available | Not Available | Not Available |
| Titanium dioxide - (13463-67-7) | Not Available | Not Available | Not Available |
| Zircon - (14940-68-2) | Not Available | Not Available | Not Available |
| FELDSPAR - (68476-25-5) | Not Available | Not Available | Not Available |
| Manganese compounds (as Mn) - (7439-96-5) | 40.00, Daphnia magna | Not Available | Not Available |
| Molybdenum - (7439-98-7) | Not Available | Not Available | Not Available |
| Niobium - (7440-03-1) | Not Available | Not Available | Not Available |
| Aluminum oxide - (1344-28-1) | Not Available | Not Available | Not Available |
| Sodium fluoride - (7681-49-4) | Not Available | Not Available | Not Available |

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

| | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA |
|---|--|---|----------------------------------|
| 14.1. UN number | Not Applicable | Not Regulated | Not Regulated |
| 14.2. UN proper shipping name | Not Regulated | Not Regulated | Not Regulated |
| 14.3. Transport hazard class(es) | DOT Hazard Class: Not Applicable | IMDG: Not Applicable Sub Class: Not Applicable | Air Class: Not Applicable |
| 14.4. Packing group | Not Applicable | Not Applicable | Not Applicable |
| 14.5. Environmental hazards | | | |
| IMDG | Marine Pollutant: No | | |
| 14.6. Special precautions for user | No further information | | |

15. Regulatory information

| | |
|---|---|
| Regulatory Overview | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. |
| Toxic Substance Control Act (TSCA) | All components of this material are either listed or exempt from listing on the TSCA Inventory. |
| WHMIS Classification | D2A |
| US EPA Tier II Hazards | Fire: No Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes |
| EPCRA 311/312 Chemicals and RQs (lbs): | Chromium compounds (as Cr (III)) (5,000.00) Nickel (100.00) Sodium fluoride (1,000.00) |
| EPCRA 302 Extremely Hazardous: | To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. |

EPCRA 313 Toxic Chemicals:

Chromium compounds (as Cr (III))

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

Manganese compounds (as Mn)

Nickel

Proposition 65 - Carcinogens (>0.0%):

Nickel

Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Aluminum oxide

Chromium compounds (as Cr (III))

Manganese compounds (as Mn)

Molybdenum

Nickel

Sodium fluoride

Titanium dioxide

Pennsylvania RTK Substances (>1%):

Aluminum oxide

Chromium compounds (as Cr (III))

Manganese compounds (as Mn)

Molybdenum

Nickel

Sodium fluoride

Titanium dioxide

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H301 Toxic if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Safety Data Sheet

Stainless Flux-Cored Wire

SDS Revision Date:

09/15/2015

H319 Causes serious eye irritation.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Midalloy believes that the information contained in this SDS is accurate. However, Midalloy does not express or imply any warranty with respect to this information.

End of Document